

TIL

22087 - black
22088 - white




oktaplex
motion



DE - Montageanleitung
FR - Instructions de montage
ES - Instrucciones de montaje
IT - Istruzioni per il montaggio

NL - Montage-instructies
SE - Monteringsanvisningar
CZ - Návod k montáži
SK - Návod na montáž

RO - Instrucțiuni de montaj
PL - Instrukcje montażu
GB - Mounting instructions
PT - Instruções de montagem



Compatible with most standard switch series with internal module dimensions of 55 mm x 55 mm (square internal corners only)

Kompatibel mit den meisten gängigen Schalterserien im Modulinnenmaß von 55 mm x 55 mm (nur für quadratische/eckige Innenecken geeignet)

Infrarot Bewegungsmelder für Innen / Détecteur de mouvement infrarouge pour l'intérieur /
 Detector de movimiento por infrarrojos para interiores / Rilevatore di movimento a
 infrarossiper interni / Infrarood bewegingsmelder voor binnen / Infraröd rörelsedetektor för
 inomhus / Infracervený detektor pohybu pro interiér / Infracervený detektor pohybu pre
 interiér / Detector de mișcare în infraroșu pentru interior / Czujnik ruchu na podczerwień
 do użytku wewnątrz / Infrared motion detector for indoors / Detetor de movimentos por
 infravermelhos para interiores

Nennspannung / Tension nominale / Tensión nominal / Tensione nominale / Nominaal voltage
 / Märkspänning / Jmenovitě napětí / Menovitě napätie / Tensiunea nominală / Napięcie
 nominalne / rated voltage / Tensão nominal

AC 220-240 V
 50-60 Hz

Nennleistung / Puissance nominale / Potencia nominal / Potenza nominale / Nominaal
 vermogen / Märkeffekt / Jmenovitý výkon / Menovitý výkon / Putere nominală / Moc znamie-
 nowa / rated power / Potência nominal

0,5 W

Maximale Schaltlast / Charge maximale commutable / Carga máxima de conmutación / Carico
 massimo commutabile / Maximale schakelbelasting / Maximal kopplingsbelastning / Maximální
 spínací zátěž / Maximálne spínacie zaťaženie / Sarcina maximă de comutare / Maksymalne
 obciążenie przętaćzające / Maximum switching load / Carga máxima de comutação

 500 W

  200 W

Minimale Schaltlast / Charge de commutation minimale / Carga de conmutación mínima /
 Carico minimo di commutazione / Minimale schakelbelasting / Minimal kopplingsbelastning
 / Minimální spínací zátěž / Minimálne spínacie zaťaženie / Sarcina minimă de comutare /
 Minimalne obciążenie przętaćzające / Minimum switching load / Carga mínima de comutação

2 W

Schutzklasse / Indice de protection / Clase de protección / Classe di protezione / Bescher-
 mingsklasse / Skyddsklass / Třída ochrany / Trieda ochrany / Clasa de protecție / Klasa
 ochrony / Protection class / Classe de protecção

II

Schutzart / Indice de protection IP / grado de protección / Livello di protezione IP / IP mate-
 van bescherming / IP-klass / Stupeň ochrany / Stupeň IP ochrany / Clasa de protecție IP /
 Klasa ochrony IP / Protection class / Tipo de protecção

IP20


Umgebungstemperatur / Température ambiante / Temperatura ambiente / Temperatura
 ambiente / Omgevingstemperatuur / Omgivningstemperatur / Okolní teplota / Okolná teplota /
 Temperatura ambiantă / Temperatura otoczenia / Ambient temperature / Temperatura ambiente

-20 °C - +40 °C




INSTALLATION


1



2




3





4




Option 1
two wire connection



Option 2
three wire connection



INSTALLATION



INSTALLATION - TWO WIRE


Master-Slave

i

max. Load


500 W 

200 W  




INSTALLATION - THREE WIRE

Master-Slave




i max. Load
500 W
200 W

Master-Master



SETTINGS



OFF

schaltet das angeschlossene
Gerät dauerhaft aus

Switches the connected
device off permanently


ON

schaltet das angeschlossene
Gerät dauerhaft an



Switches the connected
device on permanently

PIR

Sensor- Modus
sensor mode



SETTINGS



ETAPLEX GmbH · Höherweg 245 · 40231 Düsseldorf · Germany
+49 211 9726 4070 · info@etaplex.de · oktaplex.de